



VHX-69C-NOV Dakota Digital VHX Instrument Installation For 1969-76 Nova

1973-75 Buick Apollo 1975-76 Buick Skylark 1973-76 Oldsmobile Omega 1971-76 Pontiac Ventura



Installation

1. Remove the stock gauge bezel and cluster from the dash. Retain all hardware for reassembly



2. Remove the eight (8) screws holding the gauges to the bezel and save the screws for reassembly.



3. With the stock gauges out of the way, place the new VHX gauge assembly in the bezel with the long mounting tabs towards the top. Attach the gauge cluster to the bezel using the stock screws from disassembly.



4. Connect one end of the CAT5 cable to the system as the assembled cluster is installed into the dash, take care when routing this cable to the control box.



5. Re-install the assembled cluster into the vehicle and refer to the main manual for wiring instructions to complete the VHX installation.



MWARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North Sioux Falls, SD 57107 Fax www.dakotadigital.com dakotasupport@dakotadigital.com Copyright 2011 - Dakota Digital, Inc.

Phone (605) 332-6513 (605) 339-4106