



HDX-64C-PU

Dakota Digital HDX Instrument Installation
For 1964-'66 Chevy Pickups

Your new HDX-64C-PU kit includes:

HDX Display



Universal Sender Pack

Buzzer

Installation Manuals

7x Screws



Foam Tape




Main Harness


Control Box

Installation

1. Remove the stock gauge cluster from the dash.




2. Remove the stock gauges, separator plate, and lens from the bezel. The only item to be reused is the original front bezel; the other pieces can be set aside. Cut the supplied foam tape into six pieces, so each is about two inches long. Stick the foam strips on the angled part of the inside edge of the bezel. The lens will compress against any foam above the edge, which helps prevent lens rattles.




3. Secure the HDX system to the bezel with the seven supplied screws.



4. Connect the provided harness and the buzzer (optional for audio feedback) to the back of the HDX system.



5. Re-install the cluster into the truck and refer to the main manual for wiring instructions to complete the HDX installation.



⚠️WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North
Sioux Falls, SD 57107
www.dakotadigital.com
dakotasupport@dakotadigital.com Phone (605) 332-6513
Fax (605) 339-4106
Copyright 2011 - Dakota Digital, Inc.