



VHX-49C

Dakota Digital VHX Instrument Installation
For 49-50 Chevy Car System

Your new **VHX-49C** kit should include:

VHX Display



Universal Sender Pack



Switch Assembly



Installation Manuals



CAT5 Cable



Control Box

Installation

- 1a. Remove the stock gauges from the dash. Remove the two hex nuts from behind the dash from the bolts that go through the upper two tabs.



- 1b. After the hex nuts are removed you can slide the system off of the bolts and lift system off the two lower tabs.

2. Remove the stock gauges, and lens from the bezel. The only item to be reused is the original front bezel and the two hex nuts; the other pieces can be discarded. Now is a good time to clean the bezel and remove any dirt or old lens gasket material.



3a. Remove the protective tape from the clear lens and install the VHX system into the bezel. Watch carefully as you insert the system so you don't scratch or damage the lens.



3b. Line the slots on the edge of the new system with the flanges on the original bezel and slip them together.



4. The VHX system should align tightly and the lens should sit flush with the bezel.



5. Connect the CAT5 cable to the system so it can be routed and connected to the control box as the system is re-installed

6. Re-install the cluster into the car and refer to the main manual for wiring instructions to complete the VHX installation.



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North
Sioux Falls, SD 57107
www.dakotadigital.com

dakotasupport@dakotadigital.com Copyright 2011 - Dakota Digital, Inc.

Phone (605) 332-6513
Fax (605) 339-4106