



VHX-90C-CAM

Dakota Digital VHX Instrument Installation
For 1990-'92 Chevrolet Camaro

Your new VHX-90C-CAM kit includes:



Installation

1. First, remove the lower column cover and gauge bezel to access the stock gauge cluster. Retain all factory hardware for reassembly.



2. Remove the stock gauge cluster from the dash by removing the four (4) screws, retain the hardware for reassembly.



3. The inner gauge panel and column dust seal will be reused so remove the six (6) screws that secure the clear lens and also the additional three (3) screws on top that mounts the inner gauge panel. Save all hardware for reassembly.

Items to Reuse



4. Press the column dust cover over the pegs on the VHX system and mount the inner gauge panel using seven (7) of the factory screws.



5. Attach the provided CAT5 cable to the back of the VHX system and carefully route the open end to the control box mounting location before reassembly of the dash.



6. Mount the VHX gauge to the dash using the four (4) factory screws.



7. Re-install the gauge cluster bezel and lower panel to the dash using the factory hardware and refer to the main manual for wiring instructions to complete the VHX installation.



⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



4510 W. 61st St. North
Sioux Falls, SD 57107
www.dakotadigital.com

dakotasupport@dakotadigital.com Copyright 2011 - Dakota Digital, Inc.

Phone (605) 332-6513
Fax (605) 339-4106